

IRCCF® P10 PRO CLASS

VEHICLE RULES 2023 V23.0

Effective from Mar 17, 2023 until withdrawal

1. Preliminary Provisions

1.1. IRCCF®

- 1.1.1. The IRCCF® P10 Pro Class Vehicle Rules are compiled and maintained by the International Radio Controlled Rock Crawler Competitors Federation, hereafter referred to as IRCCF® proudly based on the actual [WRCCA ruleset](#) with possible minor modifications as localisation.
- 1.1.2. The original WRCCA Pro class rules are the intellectual property of [WRCCA](#), IRCCF® has compiled this ruleset with maximum respect for them.
- 1.1.3. Periodic rule changes - in special and justified cases - may be initiated by WRCCA or IRCCF® only.
- 1.1.4. IRCCF® may act at any time during the preparation of the competition events, during the competitions and after the competitions and change anything that IRCCF® believes is against the interest of the sport, including the interpretation of existing rules if it is discovered that a rule can be used or interpreted against the sporting spirit of the competition format.
- 1.1.5. Depending on the character and/or the urgency of the matter, IRCCF® will consider the sporting interest before anybody's financial interest, including the Licensee's interest.

2. General Specifications

- 2.1. Vehicles should resemble a 1:1 vehicle.
- 2.2. All vehicle specification measurements are to be taken in the vehicle's ready to run condition while sitting on a flat surface.
- 2.3. The vehicle's roof must be raised a minimum of 1"/25.4mm from the main chassis to resemble a cockpit. The frame sides must be an overall minimum of 1"/25.4mm tall. The cockpit & frame side are to be measured vertically from where the hood intersects the cab.
- 2.4. Protruding elements (nuts, bolts, washers, spacers, etc.) shall not be included in the measurements of the vehicle.
- 2.5. Vehicle wheelbase is limited to a maximum of 12.5"/317.5mm.
- 2.6. Vehicle track width is limited to a maximum of 12.5"/317.5mm.
- 2.7. Vehicle body/ bodiless measurements must be greater than or equal to 8"/203.2mm overall length, 3"/76.2mm overall width and 3"/76.2mm overall height.
- 2.8. There are no limitations on the amount of radio channels used on a vehicle.
- 2.9. Winching down of the axles is allowed. The winch line must be attached within a 1/2"/12.7mm of the centre of the axle and by a single attachment point only.

3. Tires & Wheels

- 3.1. Vehicles are limited to 4-wheeled vehicles only. These 4 wheels can be the only source of propulsion for the vehicle.
- 3.2. Wheel rim outer diameter is limited to 2.2"/55.88mm or smaller at the bead surface. Wheels may be modified until the tire bead surface does not exceed 2.2"/55.88mm in diameter. With a tire mounted, no exterior component of the wheel, including but not limited to, the bead lock ring shall exceed 2.55"/64.77mm.

- 3.3. Tires may be modified from other size tires using only pliable rubber, but must not exceed a total uncompressed outer diameter of 6"/152.4mm.

4. Drive Train

- 4.1. Vehicles are limited to 2-wheel steering only.
- 4.2. Motor mount can be part of or directly coupled to an axle.
- 4.3. Limited to two motors.

5. Glossary of Terms

- 5.1. **Active Suspension:** A suspension that is interlinked (such as the 1:1 Scorpion, excluding the air bags used to raise and lower the vehicle) which by design moves part of the suspension in one direction when moved from another. This does not have any driver input to be legal.
- 5.2. **Body:** Formed as a single piece of seamless rigid material, integrating roof, door (sides), and hood sections.
- 5.3. **Vehicle track width:** Is measured from the outermost edge of a tire to the outermost edge of a tire.
- 5.4. **Wheelbase:** is measured from centre of axle nut to centre of axle nut. The vehicle should be set down on a flat surface by the driver. The front wheel on the side that is being checked, must be pointing straight forward. At that time, the driver will then cycle the suspension through its complete extension and compression range while the judge measures the vehicle's maximum wheelbase. At any point the vehicle's wheelbase cannot extend beyond the maximum limit of its class. All the above procedures must be duplicated on the opposite side. Note: All vehicles will be teched in the same ready to run condition, and set up as the vehicle will be run on the course. If the vehicle's wheelbase is affected by radio control it must be cycled or activated during tech inspection.

6. Licence & Copyright

- 6.1. ©2021-2023 IRCCF Licensing Ltd. All rights reserved. The copyright and licence rights of these competition rules are the property of IRCCF Licensing Ltd. Any person acting on behalf of IRCCF Licensing Ltd. is entitled to copy, print and distribute these competition rules, subject to the following conditions:
 - 6.1.1. The contents of this document are for information purposes only, their use for commercial purposes is prohibited and will result in legal consequences.
 - 6.1.2. Any copy, in whole or in part, of this document must include this copyright notice.
- 6.2. The ISRCC™ International Scale Rock Crawler Championship, IRCCF® International Radio Controlled Rock Crawler Competitors Federation and related names, trademarks, contents and the content of the <https://irccf.org> website are the licence, copyright and intellectual properties of IRCCF Licensing Ltd.
- 6.3. These properties may only be distributed or exploited with the written permission of the rights holder, and their unauthorised use will result in legal consequences.